Corporate Supply Arrangement CS-000478

Supplier
Sharp's Audio-Visual Ltd.
12 – 1950 Government Street
Victoria, BC V8T 4N8
Ph. 250-385-3458
Fx. 250-381-2626

Supplier Contact
Greg Johnston-Watson
12 – 1950 Government Street
Victoria, BC V8T 4N8
Direct Ph. 250-294-7937
Fx. 250-381-2626
Em. gregjw@sharpsav.com

Supplier Contact
Rhonda Metcalfe
12 – 1950 Government Street
Victoria, BC V8T 4N8
Direct Ph. 250-294-7936
Fx. 250-381-2626
Em. rhonda.metcalfe@sharpsav.com

Projector Info	Brand		Panasonic	Panasonic	Panasonic	Panasonic	Panasonic	Panasonic
	Model No.		PTLW80NTU	PTLB80NTU	PTLB80U	PTLB75NTU	PTLB75U	PTLB51U
Basic Info	Display	(Device)	0.59 x3LCD	0.63 x3LCD	0.63 x3LCD	0.63 x3LCD	0.63 x3LCD	0.6 x3LCD
	Pixel Number	(Native)	1280x800	1024x768	1024x768	1024x768	1024x768	1024x768
		(Max)	1600x1200	1600x1200	1600x1200	1600x1200	1600x1200	1600x1200
	Aspect Ratio		16:10	4:3	4:3	4:3	4:3	4:3
	Brightness	High mode	2600 lm	3200 lm	3200 lm	2600 lm	2600 lm	2000
		Low/Eco mode	2130lm	2620lm	2620lm	2130lm	2130lm	No
	Contrast ratio		500:1	500:1	500:1	500:1	500:1	400:1
	Lens Zoom Ratio		1:1.2	1:1.2	1:1.2	1:1.2	1:1.2	1:1.2
	Focal length		f=18.8~22.6mm	f=18.8~22.5mm	f=18.8~22.5mm	f=18.5~22.2mm	f=18.5~22.2mm	f=18.8~22.6mm
	Power		100V-240 AC 50/60Hz	100V-240 AC 50/60Hz	100V-240 AC 50/60Hz	100V-240 AC 50/60Hz	100V-240 AC 50/60Hz	100V-240 AC 50/60Hz
	Power consumption	Operation	300W	300W	300W	300W	300W	240W
		Standby	3W	4W	4W	4W	4W	4W
	Speaker		1W	1W	1W	1W	1W	1W
	Size	Width	368mm 14.49"	368mm 14.49"	368mm 14.49"	368mm 14.49"	368mm 14.49"	297mm 11.69"
		Height	88mm 3.46"	88mm 3.46"	88mm 3.46"	88mm 3.46"	88mm 3.46"	57mm 2.24"
		Depth	233mm 9.17"	233mm 9.17"	233mm 9.17"	233mm 9.17"	233mm 9.17"	210mm 8.27"
	Weight		2.96kg	2.96kg	2.96kg	2.96kg	2.96kg	1.8kg
Input Terminals	Video	Input	1	1	1	1	1	1
	SVideo	Input	1	1	1	1	1	1
	Computer	D-Sub15p	1	1	1	2	2	2
		Monitor out	1	1	1	1	1	1
	Serial (RS232C)	Input	1	1	1	1	1	1
	Wireless LAN		802.11b/g	802.11b/g	No	802.11b/g	No	No
	Audio	Input	2	2	2	2	2	2
		Output	1	1	1	1	1	1
Reliability	Lamp	(W)	220W	220W	220W	220W	220W	165W
	Lamp life time	(Normal)	3000h	3000h	3000h	3000h	3000h	3000h
	Noise	(High or STD)	35dBA	35dBA	35dBA	35dBA	35dBA	33dBA
		(Low or Eco)	29dBA	29dBA	29dBA	29dBaA	29dBaA	No
	Operation Temperature		0°C to 40°C	0°C to 40°C	0°C to 40°C	0°C to 40°C	0°C to 40°C	0°C to 40°C
Other Features	Remote Control		Yes	Yes	Yes	Yes	Yes	Yes
	Carrying Case		Yes	Yes	Yes	Yes	Yes	Yes
	others		Daylight View4	Daylight View4	Daylight View4	Daylight View4	Daylight View4	Daylight View4